



SAFETY DATA SHEET

Juice Endurance Sealant 1lt and 500ml

Compilation date: 01/08/2008
Revision date: 22/01/2018
Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Juice Endurance Sealant (modified)
Product code: JPEND1L , JPEND500

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Automotive care , Polish.

1.3 Details of the supplier of the safety data sheet

Sydney Automotive Paints and Equipment Pty Ltd
Unit A3, 366 Edgar Street
Condell Park 2200
NSW
Australia
www.juicepolishes.com.au
reception@sape.com.au
Phone : 02 9 772 9000
Fax ; 02 9 772 9001

1.4. Emergency telephone number

Poison Information Centre
13 11 26

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Aspiration Toxicity	Category 1	
Flammable Liquid	Category 3	
Specific Target Organ Toxicity (Repeated Exposure)		Category 1
Aquatic Toxicity Chronic	Category 3	

2.2 Label elements



- Signal Word: Danger

Hazard phrases:

H226 - Flammable liquid and vapour.



SAFETY DATA SHEET

Juice Endurance Sealant

H372 - Causes damage to organs through prolonged or repeated exposure.

H304 - May be fatal if swallowed and enters airways.

AUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P403+P235 - Store in a well-ventilated place. Keep cool.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 - Do not breathe dust/fume/ gas/mist/ vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P314 - Get medical advice/attention if you feel unwell.

P370+P378 - In case of fire: use foam, carbon dioxide or dry agent for extinction.

P273 - Avoid release to the environment.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

2.3 Other hazards

Section 3: Composition/information on ingredients

3.1 Mixtures

- Distillates (petroleum), hydrotreated light; Kerosene - unspecified
 - CAS Number: 64742-47-8
 - EC Number: 265-149-8
 - Concentration: 1-5%
 - Categories: Asp. Tox. 1
 - Symbols: GHS08
 - Statements: H304
- Hydrocarbons, C9-12, n-alkanes, isoalkanes, Cyclics, Aromatics (2-25%)
 - CAS Number: 64742-88-7
 - EC Number: 919-446-0
 - Concentration: 10-20%
 - Categories: STOT SE 3, STOT RE 1, Asp. Tox. 1
 - Symbols: GHS02, GHS07, GHS08, GHS09
 - Statements: H226, H304, H336, H372, H411
- Bis (2-hydroxyethyl) oleyl amine
 - CAS Number: 25307-17-9
 - EC Number: 246-807-3
 - Concentration: <1%
 - Categories: Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B
 - Symbols: GHS05, GHS07, GHS09
 - Statements: H302, H314, H400

Section 4: First aid measures

4.1. Description of first aid measures

- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].



SAFETY DATA SHEET

Juice Endurance Sealant

- P301+P310 - IF SWALLOWED: Immediately call a POISON INFORMATION CENTRE on 13 11 26 or doctor/physician.
- P331 - Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Mildly irritating to respiratory system.
- In cases of severe exposure, dizziness, confusion, headache or stupor may develop.
- Mildly irritating to skin and eyes.
- Can cause damage to the eyes, skin and mucous membranes.

4.3 Indication of any immediate medical attention and special treatment needed

- Seek medical attention if irritation persists.
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 - Do NOT induce vomiting.

Section 5: Fire-fighting measures

5.1 Extinguishing media

- P370+P378 - In case of fire: use foam, carbon dioxide or dry agent for extinction.

5.2 Special hazards arising from the substance or mixture

- May give off noxious and toxic fumes in a fire.
- Smoke from fires is irritating. Take precautions to protect personnel from exposure.

5.3 Advice for firefighters

- Keep container(s) exposed to fire cool, by spraying with water.
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
- Wear Breathing Apparatus.

HAZCHEM: •3Y

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Spillage causes slippery surface.
- Shut off source of leak if safe to do so.
- Ensure adequate ventilation.

6.2 Environmental precautions

- Do not empty into drains.
- Do not allow to enter public sewers and water courses
- If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities.
- P273 - Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

- Absorb spillage in inert material and shovel up.
- Place in appropriate container.
- Remove contaminated material to safe location for subsequent disposal.
- To clean the floor and all objects contaminated by this material use soap and water.

6.4 Reference to other sections

- See Section 3, 8 & 13 for further information.



SAFETY DATA SHEET

Juice Endurance Sealant

Section 7: Handling and storage

7.1 Precautions for safe handling

- Ensure adequate ventilation.
- Proper chemicals handling procedures should be adopted.
- P264 - Wash hands thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P314 - Get medical advice/attention if you feel unwell.
- P501 - Dispose of contents/container to responsible waste disposal company.

7.2 Conditions for safe storage, including any incompatibilities

- Keep in a cool, dry, well ventilated place.
- P404 - Store in a closed container.
- Keep away from frost.
- P403+P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.

7.3 Specific end use(s)

- No hazardous reactions known if used for its intended purpose.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Exposure limits

- Distillates (petroleum), hydrotreated light; Kerosene - unspecified
WEL TWA (long term): 200 mg/m³ (EU)
- Hydrocarbons, C9-12, n-alkanes, isoalkanes, Cyclics, Aromatics (2-25%)
WEL TWA (long term): 330 mg/m³ (EU)

8.2 Exposure controls



- P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance: white, viscous cream
- Odour: characteristic odour
- Specific Gravity: 0.980



SAFETY DATA SHEET

Juice Endurance Sealant

- Flash point: 53 °C
- Viscosity: 15,000 centipoises at 20 °C
- Solubility in water: Partly soluble in water

9.2 Other information

- Volatile Organic Compound Content: <25%

Section 10: Stability and reactivity

10.1 Reactivity

- This article is considered stable under normal conditions.

10.2 Chemical stability

- This article is considered stable under normal conditions.

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

- Keep away from frost.

10.5 Incompatible materials

- No hazardous reactions known if used for its intended purpose.

10.6 Hazardous decomposition products

- No hazardous decomposition products known.

Section 11: Toxicological information

11.1 Information on toxicological effects

- No information available but must be considered harmful.
- Causes damage to organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.
- Mildly irritating to respiratory system.
- In cases of severe exposure, dizziness, confusion, headache or stupor may develop.
- Mildly irritating to skin and eyes.
- Can cause damage to the eyes, skin and mucous membranes.

Section 12: Ecological information

12.1 Toxicity

- Distillates (petroleum), hydrotreated light; Kerosine - unspecified
 - IC50 (algae): >100 mg/l (72 hr)
 - EC50 (daphnia): >100 mg/l (48 hr)
 - LC50 (fish): >100 mg/l (96 hr)
- Hydrocarbons, C9-12, n-alkanes, isoalkanes, Cyclics, Aromatics (2-25%)
 - IC50 (algae): 10 mg/l (72 hr)
 - EC50 (daphnia): 2.2 mg/l (48 hr)
 - LC50 (fish): 3.0 mg/l (96 hr)
- Bis (2-hydroxyethyl) oleyl amine
 - IC50 (algae): >1 mg/l (72 hr)
 - EC50 (daphnia): >1 mg/l (48 hr)



SAFETY DATA SHEET

Juice Endurance Sealant

LC50 (fish): 0.5 mg/l (96 hr)

12.2 Persistence and degradability

- Biodegradable

12.3 Bioaccumulation Potential

- Low bioaccumulation potential.

12.4 Mobility in soil

- No information available.
- Partly miscible with water.

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII

12.6 Other Adverse Effects

- No information available.

Section 13: Disposal considerations

13.1 Waste treatment methods

- Do not empty into drains.
- Do not pierce or burn container, even after use.
- Do not reuse empty containers without commercial cleaning or reconditioning.
- P501 - Dispose of contents/container to responsible waste disposal company.

Section 14: Transport information



14.1 UN Number

- UN No.: 1139

14.2 Proper Shipping Name

- Proper Shipping Name: COATING SOLUTION

14.3 Transport hazard class(es)

- Hazard Class: 3

14.4 Packing group

- Packing Group: III

14.5 Environmental hazards

- Presents little or no hazard to the environment

14.6 Special precautions for user

- ADR Classification Code: 30
- ADR Hazard Class: 3



SAFETY DATA SHEET

Juice Endurance Sealant

- Tunnel Code: D/E

Sea (IMDG)

- IMDG EmS: F-E, S-E

- IMDG Hazard Class: 30

14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE

- No information available

HAZCHEM Code: •3Y

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- A chemical safety assessment is not required under REACH
- This Safety Data Sheet is provided in compliance with the Chemicals (Hazard Information and Packaging) Regulations.
- This SDS was prepared in accordance to European Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
- Water Hazard Class (Company): Not hazardous

Section 16: Other information

Flammable liquid and vapour. H302: Harmful if swallowed. H304: May be fatal if swallowed and enters airways. H314: Causes severe skin burns and eye damage. H336: May cause drowsiness or dizziness. H372: Causes damage to organs through prolonged or repeated exposure. H400: Very toxic to aquatic life. H411: Toxic to aquatic life with long lasting effects.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication; however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other processes.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.